

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 475 610 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 24.05.95 (51) Int. Cl.⁶: **F02M 37/22, B01D 35/027, F02M 37/10**

(21) Application number: **91307698.0**

(22) Date of filing: **21.08.91**

(54) **Fuel tank filter.**

(30) Priority: **27.08.90 US 572761**

(43) Date of publication of application:
18.03.92 Bulletin 92/12

(45) Publication of the grant of the patent:
24.05.95 Bulletin 95/21

(84) Designated Contracting States:
DE ES FR GB IT

(56) References cited:
EP-A- 0 369 039
US-A- 4 312 753

PATENT ABSTRACTS OF JAPAN, vol. 11, no.
228 (M-610)(2675) 24 July 1987 & JP-A-62 041
962 (NISSAN) 23 February 1987

XX FISITA CONGRESS, pages 2.154 to 2.161

(73) Proprietor: **FILTERTEK, INC.**
P.O. Box 135
Price Road
Hebron
Illinois 60034 (US)

(72) Inventor: **Cain, Thomas A.**
13821 Sunset Ridge
Woodstock,
Illinois 60098 (US)

(74) Representative: **Alexander, Thomas Bruce et al**
Boult, Wade & Tennant
27 Furnival Street
London EC4A 1PQ (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

which are conventional and none of which are shown) to the top of the tank 10. The present invention is designed for instances where the bottom 14 of the fuel tank, for one reason or another, moves up and down with respect to the fuel pump 12. As discussed above, this situation is most common where the fuel tank 10 is made of plastic, and the pump 12 is fixed to the top of the fuel tank 10.

The filter 20 attaches to the inlet 16 on the bottom of the pump 12. As shown in Figures 2 and 4, the filter 20 of the preferred embodiment includes a filtration material envelope 22 and a molded plastic separator element 30. The separator 30 is used to hold the envelope 22 open to improve fuel flow through the envelope 22. Preferably the envelope is made of a nylon screen material 24. The screen 24 is welded closed on its side and bottom ends by welds 28 to form the envelope shape.

The separator element 30 has a generally planer back 40 with upstanding projections 42 molded integrally therewith, best seen in Fig. 3. The projections 42 help to hold the walls of the envelope 22 away from each other and the back 40. As best shown in Figure 2, the separator 30 has a fitting 32 integrally molded to its central section. The fitting 32 includes four holes 36 at 90° intervals around the bottom of the fitting 32. The holes 36 allow fuel from the envelope 22 to flow to the pump inlet 16. The screen 24 is sealed in between a top shoulder on fitting 32 and a bottom shoulder of a connector 34. The connector 34 is designed to fit over the end of the fuel pump inlet 16. A tab 35 at the top of the connector 34 includes a hole 38. A pin or tang 18 (Fig. 1) extending from the bottom of the fuel pump 12 fits through hole 38 to align the filter 20. Also, a fastener on the end of pin 18 may be used to secure the filter 20 to the pump inlet 16.

A spring 50, preferably made from flat stock spring steel, is attached to the back 40 on each side of the filter 20. The spring 50 is preferably in a bowed shape in its untensioned state. Thus, when it is attached to the back 40, it will tend to pull the filter 20 into the shape shown in Fig. 2. When the bottom of the tank 14 rises to its higher level (shown in phantom lines in Fig. 1), the tank bottom 14 pushes up on the filter 20, spreading the two sides apart so that the filter 20 takes the shape shown in phantom lines in Fig. 1. This movement of course puts the spring 50 into a tensioned state. When the tank bottom 14 drops, the spring 50 pushes the two sides of filter 20 into their original position, which holds the filter material envelope 22 against the bottom 14 of the fuel tank.

The spring 50 is preferably attached to the back 40 by being placed in channels 40 molded onto the back 40, as best seen in Fig. 3. The spring 50 could also be embedded in the back 40

during molding. During assembly of the preferred embodiment, the left end of spring 50 is slid through the channels 48 (skipping the far right channel), going from right to left, and coming to a stop in end channel 40 on the far left. The far right channel is somewhat open on the bottom so that the end of spring 50 can snap up into place.

In the preferred embodiment, the spring 50 is about 1.6cm (5/8 of an inch) wide and 0.03cm (0.012 inches) thick. The filter envelope 22 is about 4.4cm (1-3/4 inches) wide and 21.6cm (8-1/2 inches) long. The separator element 30 is about 2.9cm (1-1/8 inches) wide and 13.9cm (5-1/2 inches) long. The back 40 is about 0.13cm (0.050 inches) thick. If desired, holes may be made through the back 40 to allow for improved fuel flow inside the envelope 22. The projections 42 are about 0.23cm (0.090 inches) in diameter and 0.8cm (5/16 of an inch) high. The separator 30 and connector 34 are preferably made from acetal resin, though they could also be made from nylon. The preferred screen 24 has a 180 by 38 mesh, and is capable of removing impurities 60 microns or larger. The fitting 32 and connector 34 are preferably secured together and sealed around the screen 24 by sonic welding.

A filter 120 of a second embodiment of the invention is shown in Figs. 5 and 6. The filter 120 is not as long as the filter 20, and thus extends to only one side of the pump inlet. For the most part, it has the same elements as the filter 20. For this reason, the elements of the two embodiments are numbered with the same reference numbers, increased by 100 for the filter 120.

There are, of course, several differences. In the filter 120, the screen 124 is held into a rigid coupling element 126 by having the coupling 126 molded around it. The coupling 126 is designed to snap onto the end 128 of the separator element 130 after the separator element 130 is inserted into the envelope 122. The end 128 of the separator element 130 fits inside of connector 134. The connector 134 is in the shape of an elbow that connects directly to the pump inlet 16.

The back 140 includes holes 144 to allow fuel to more easily flow into the envelope 122 through the screen 124 on the bottom side of the filter 120. The back 140 is integrally molded with the end 128. However, the back 140 may pivot up and down compared to the connector 134. The spring as shown is embedded in the plastic making up the back 140. The spring 150 may also be held to the back 140 by screws or other methods, such as the channels 48 in the filter 20.

zum Formen des Trennteils (30) verwendet wird.

7. Kraftstofftankfilter nach Anspruch 1, wobei das Trennteil (30) ein im allgemeinen planes Rückenelement mit Vorsprüngen (42) umfaßt, die sich von wenigstens einer Fläche daran erstrecken. 5
8. Kraftstofftankfilter nach Anspruch 1, wobei sich die Feder (50) zwischen dem Anschlußteil (34) und dem Trennteil (30) erstreckt. 10
9. Kraftstofftankfilter nach Anspruch 8, wobei das Trennteil (30) aus Kunststoff besteht und das Trennteil (30) an die Feder (50) geformt ist. 15
10. Kraftstofftankfilter nach Anspruch 1, wobei sich die Feder (50) im Inneren der Hülle (22) befindet. 20
11. Kraftstofftankfilter nach Anspruch 1, wobei die Feder (50) aus einem Material besteht, das in seiner Funktion durch den Kontakt mit Benzin, das Alkohol enthält, nicht beeinträchtigt wird. 25
12. Kraftstofftankfilter nach Anspruch 1, wobei sich die Feder (50) in mehr als einer Richtung von dem Anschlußteil (34) aus erstreckt. 30
13. Kraftstofftank nach Anspruch 1, wobei das Anschlußteil (34) ein zweiteiliges Element (32, 34) umfaßt, und das Filtermaterial (24) zwischen aneinandergrenzenden Flanschen der beiden Teile eingeschlossen ist. 35

Revendications

1. Filtre (20) pour réservoir de carburant, comprenant : 40
 - (a) un matériau de filtration (24) formant une enveloppe (22),
 - (b) un séparateur (30) formé de matière plastique, disposé dans l'enveloppe (22) et destiné à maintenir l'enveloppe (22) sous forme ouverte et à rappeler l'enveloppe (22) vers le fond du réservoir (14) de carburant, et 45
 - (c) un raccord (34) destiné à connecter l'enveloppe (22) à l'entrée (16) de la pompe (12) de carburant, le raccord (34) formant une connexion non souple entre le séparateur (30) et l'entrée (16) de la pompe, 50
 caractérisé en ce que le filtre comporte en outre un ressort métallique plat (50), et le ressort (50) et le séparateur (30) sont fixés l'un à l'autre afin qu'ils forment un ensemble combiné qui joue le rôle d'un 55

seul élément destiné à rappeler l'enveloppe (22) vers le fond du réservoir (14) de carburant.

2. Filtre pour réservoir de carburant selon la revendication 1, dans lequel l'enveloppe de filtre et le séparateur (30) sont allongés et sont placés des deux côtés de l'entrée (16) de la pompe.
3. Filtre pour réservoir de carburant selon la revendication 2, dans lequel le ressort (50) a une forme bombée à l'état sans tension et est fixé au séparateur (30) des deux côtés de l'entrée (16).
4. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) est un ressort plat d'acier.
5. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) se loge dans un canal (48) moulé sur le séparateur (30).
6. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) est incorporé à de la matière plastique utilisée pour le moulage du séparateur (30).
7. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le séparateur (30) comporte un organe arrière plan de façon générale et ayant des saillies (42) dépassant d'une face au moins.
8. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) recouvre l'espace compris entre le raccord (34) et le séparateur (30).
9. Filtre pour réservoir de carburant selon la revendication 8, dans lequel le séparateur (30) est formé de matière plastique, et le séparateur (30) est moulé sur le ressort (50).
10. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) est placé à l'intérieur de l'enveloppe (22).
11. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) est formé d'un matériau dont le fonctionnement n'est pas affecté par le contact de l'essence contenant de l'alcool.
12. Filtre pour réservoir de carburant selon la revendication 1, dans lequel le ressort (50) dé-

FIG-1-





FIG-2-

